

Litelines

Catalog #:	
Job:	
Type:	Voltage:

CPB Series

Structural

Round/Square concrete bollard with (4) top cap options, multiple device option and widths from 8-24".

Accent Band Finish

Thermoset polyester powder coating is electrostatically applied and baked to form a smooth durable maintenance free finish. Specify: Light Grey ("GY"), Black ("BK"), White ("WH") or Bronze ("BZ"). Consult factory for other colors.

Electrical

Ballast and electrical components are "UL Listed," factory prewired and mounted to a rigid support chassis for suspension within the concrete base. A heavy cast aluminum junction box with locking cover and a removable rigid aluminum mounting plate for up to (2) single gang devices.

Surface

The precast concrete shall be available in the following finishes: Mold Finish ("MF"), Sandblast ("SB") or Exposed Aggregate ("EA"). Consult factory for special aggregates and surface textures.


Color

The concrete shall be available in the following standard colors: Natural Grey Cement (N), Brown (BR), White (WH), Dark Bronze (BU), Copper (CO), and Special (SP). Consult factory for other colors.

Mounting


Anchor base bollards "AB" are supplied with plated anchor bolts for installation into a concrete footing.

Dimensions




Mounting

9.5" Bolt Circle



4" Conduit Opening



Cap Options



Ordering Information

Ordering Example: CPB-8-SQ-CPT-GFI1-18-AB-NA-NA-N-MF

